

Products	Tosi 175 	Tosi 350 	Tosi 375 	Tosi 610 	Tosi 675 	Tosi 695 
	CE, FCC, IMDA, RCM, MIC/JATE, WPC	CE, FCC, cULus, RCM	CE, FCC, cULus, RCM	CE, RCM, CB Safety, SGS Safety Mark	CE, FCC, IC, RCM, CB Safety, SGS Safety Mark, Verizon	CE, SGS Safety Mark
Connectivity	4G x 1 WLAN Ethernet	WLAN Ethernet	WLAN Ethernet LTE	Ethernet	4G x 2 WLAN Ethernet	5G/LTE Module WLAN Ethernet
DUAL SIM	No	No	No	No	Yes	Yes
LAN Ports	1(10/100Mb/s)	4(10/100Mbps)	4(10/100Mbps)	3 (10/100/1000 Mb/s)	3 (10/100/1000Mb/s)	4 (10/100/1000Mb/s)
VPN throughput	Up to 10 Mbit/s	Up to 10 Mbps	Up to 10 Mbps	Aggregate VPN throughput up to 70 Mbps. Single VPN throughput up to 25 Mbps	Aggregate VPN throughput up to 70 Mbps. Single VPN throughput up to 25 Mbps	Aggregate VPN throughput up to 70 Mbps. Single VPN throughput up to 25 Mbps
Measurements	104 mm x 28 mm x 110 mm 4.09" x 1.10" x 4.33" (L x W x H)	145 mm x 114 mm x 45 mm 5.71" x 4.49" x 1.77" (W x H x L)	145 mm x 114 mm x 45 mm 5.71" x 4.49" x 1.77" (W x H x L)	115 mm x 32.2 mm x 95.2 mm 4.52" x 1.26" x 3.74" (W x H x L)	115mm x 44.2mm x 95.1 mm 4.52" x 1.74" x 3.74" (W x H x L)	132 mm x 44 mm x 95 mm 4.52" x 1.74" x 3.74" (W x H x L)
Operating temperature	-20 °C ... +55 °C -4 °F ... +131 °F	-35 °C ... +75 °C -31 °F ... +167 °F	-35 °C ... +75 °C -31 °F ... +167 °F	-40 °C ... +75 °C -40 °F ... +167 °F	-40 °C ... +75 °C -40 °F ... +167 °F	-40 °C ... +75 °C -40 °F ... +167 °F

All devices are equipped with Built-in firewall with 1:1 NAT, End-to-end VPN, SW auto-update, Layer 2 / Layer 3, Connectivity with Tosi Ecosystem.
Access Control with Tosi Key or Tosi HUB.
Industrial plugs and DIN rail attachment are included.